



ИБП Eaton Ellipse ASR - Ellipse ASR - Информация об ИБП

Постоянная ссылка на страницу: <https://eaton-power.ru/catalog/eaton-ellipse-asr/>

# Eaton Ellipse ASR

450/600/750/1000/1500 VA



Eaton Ellipse ASR range



Eaton Ellipse ASR versatility



## Passive standby (off-line)

Protecting business computer equipment

### The highest level of protection for business computers

- Eaton Ellipse ASR UPSs not only provide a battery backed up supply to keep equipment operating when there is a power cut but also provide effective protection against damaging surges
- Ellipse ASR (Advanced Surge Reduction) UPSs include a high performance surge protective device which complies with IEC 61643-1 standards
- Ellipse ASR UPSs also protect telephone, broadband and Ethernet for complete protection

### The widest range of sockets

- 4 sockets (450/600/750 models) or 8 sockets (1000/1500 models)
- Practical: French, "Schuko" and universal sockets. Also available with IEC sockets

### The greatest flexibility

Extra flat for easy installation in all business environments:

- Vertical box format or below the desk
- Horizontal under a monitor
- 19" rack-mountable (optional 2U kit)

### The best compatibility with computer equipment

The USBS models are designed for compatibility with a wide variety of computers:

- Combined USB and serial ports
- Power management software available under Windows, Linux and Mac OS



Powering Business Worldwide



# Eaton Ellipse ASR

- 1 4 sockets with surge protection
- 2 4 sockets with surge protection and backup
- 3 Tel/broadband and Ethernet 10/100 MB protection
- 4 Combined USB / serial port
- 5 Replaceable batteries
- 6 Circuit breaker reset button



Eaton Ellipse ASR 1000/1500



Eaton Ellipse ASR 450/600/750

- 1 Combined USB/serial port (USBS models)
- 2 Tel/broadband and Ethernet 10/100 MB protection
- 3 Replaceable batteries
- 4 3 sockets with surge protection and backup and 1 socket with surge protection
- 5 Circuit breaker reset button

| TECHNICAL SPECIFICATIONS                       | 450   | 600/600 USBS                                    | 750 USBS                     | 1000 USBS                    | 1500 USBS                    | XL                |
|--|---|---|------------------------------|------------------------------|------------------------------|-------------------|
| Rating (VA/W)                                  | 450 VA / 250 W  | 600 VA / 360 W                                  | 750 VA / 450 W               | 1000 VA / 600 W              | 1500 VA / 900 W              | 420 VA / 250 W    |
| <b>Application</b>                             |   |   |                              |                              |                              |                   |
| Multi-way sockets                              | 4   | 4   | 4                            | 8                            | 8                            | 5                 |
| Sockets with surge protection and backup /     | 3/1   | 3/1   | 3/1                          | 4/4                          | 4/4                          | 4/1               |
| Sockets with surge protection for peripherals  |   |   |                              |                              |                              |                   |
| <b>Characteristics</b>                         |   |   |                              |                              |                              |                   |
| Input voltage                                  | 184 V to 264 V  | 184 V to 264 V (adjustable from 161 V to 284 V) |                              |                              |                              |                   |
| Output voltage                                 | 230 V   | 230 V (settable to 220 V, 230 V, 240 V)         |                              |                              |                              |                   |
| Frequency                                      | 50-60 Hz autoselect   |   |                              |                              |                              |                   |
| Surge protection                               | Integral surge protection device to IEC 61643-1, Total surge absorption: 525 Joules   |   |                              |                              |                              |                   |
| Circuit breaker                                | With reset  |   |                              |                              |                              |                   |
| <b>Battery</b>                                 |   |   |                              |                              |                              |                   |
| Replaceable battery                            | Compact sealed lead acid  |   |                              |                              |                              |                   |
| Battery charger                                | Operates when the UPS is under power  |   |                              |                              |                              |                   |
| Battery test                                   | Yes   | Yes   | Yes                          | Yes                          | Yes                          | Yes               |
| Cold start (no mains)                          | Yes   | Yes   | Yes                          | Yes                          | Yes                          | Yes               |
| Deep discharge protection                      | 4 hours   | 4 hours   | 4 hours                      | 4 hours                      | 4 hours                      | 48 hours          |
| Battery replacement indicators                 | LED + audible alarm   |   |                              |                              |                              |                   |
| 50% load backup                                | 11 min  | 12 min  | 12 min                       | 18 min                       | 16 min                       | 4 EXB : 15h       |
| 70% load backup                                | 6 min   | 7 min   | 6 min                        | 9 min                        | 8 min                        | 4 EXB : 9h20 min  |
| <b>Communication</b>                           |   |   |                              |                              |                              |                   |
| Communications port (USBS models)              | /   | Combined USB and serial port                    | Combined USB and serial port | Combined USB and serial port | Combined USB and serial port | /                 |
| Software supplied as standard (USBS models) /  | Compatible with: Windows Vista XP/2003/2000/98/95/Me/NT, Mandrake Linux, / Mandriva Linux, Red Hat Linux, Suse Novell, Debian GNU/Linux, Mac OS X |   |                              |                              |                              |                   |
| Line protection                                | Tel/Fax/Modem/Internet et Ethernet (available for all models)   |   |                              |                              |                              |                   |
| <b>Standards</b>                               |   |   |                              |                              |                              |                   |
| Safety   | IEC/EN 62040-1-1, CB Report, CE mark  |   |                              |                              |                              |                   |
| EMC  | IEC 62040-2   |   |                              |                              |                              |                   |
| Surge protection                               | IEC 61643-1   |   |                              |                              |                              |                   |
| <b>Mounting, colors, dimensions and weight</b> |   |   |                              |                              |                              |                   |
| Dimensions H x W x D                           | 242 x 81 x 245 mm   | 270 x 82 x 265 mm                               | 270 x 82 x 265 mm            | 305 x 80 x 312 mm            | 317 x 80 x 390 mm            | 317 x 80 x 390 mm |
| Weight   | 3 kg  | 4.2 kg  | 4.4 kg                       | 8.1 kg                       | 11 kg                        | 11 kg             |
| 19" rack mounting kit                          | 2U  | 2U  | 2U                           | 2U                           | 2U                           | 2U                |
| Color  | Black   | Titanium Grey                                   | Titanium Grey                | Titanium Grey                | Titanium Grey                | Titanium Grey     |
| <b>Customer Service &amp; Support</b>          |   |   |                              |                              |                              |                   |
| 2 years warranty                               | Standard product exchange, including the battery ; warranty for the connected computing equipment for an unlimited amount (EU countries)          |   |                              |                              |                              |                   |
| Warranty+                                      | Optional 3-years warranty (depending on the country please visit <a href="http://www.eaton.com/powerquality">www.eaton.com/powerquality</a> )     |   |                              |                              |                              |                   |

| Part Numbers          | 450    | 600    | 600 USBS | 750 USBS | 1000 USBS | 1500 USBS | XL     |
|-----------------------|--------|--------|----------|----------|-----------|-----------|--------|
| French sockets (FR)   | 66 940 | 66 765 | 66 769   | 66 773   | 66 777    | 66 781    | 66 792 |
| Schuko sockets (DIN)  | 66 941 | 66 766 | 66 770   | 66 774   | 66 778    | 66 782    | 66 793 |
| UNI sockets           | /      | 66 767 | 66 771   | 66 775   | 66 779    | 66 783    | 66 794 |
| IEC sockets           | *      | 66 768 | 66 772   | 66 776   | 66 780    | 66 784    | 66 795 |
| <b>Accessories</b>    |        |        |          |          |           |           |        |
| 19" rack mounting kit | 68 561 | 68 561 | 68 561   | 68 561   | 68 561    | 68 561    | 68 561 |
| <b>Ellipse EXB</b>    | /      | /      | /        | /        | /         | /         | 66 791 |

\* Ellipse ASR 375 IEC (66 764) available upon request.



FR DIN UNI IEC

